

<b>LUKAS</b>	<b>eDRAULIC Cutter</b>			<b>EN</b>
	<b>S 788 E2 90-20-42</b>			
	Technical Data			
<i>Non-metric dimensions are for reference only.</i>				
<b>Nomenclature</b>		<b>Value</b>	<b>Unit</b>	<b>Remark</b>
<b>Dimensions</b>	L x W x H	988 x 266 x 281 38.9 x 10.5 x 11.1	mm in.	closed; w/o battery
<b>Cutting performance</b>		Ø42 Ø1.65	mm in.	
<b>Opening width at tips</b>		200 7.87	mm in.	at tips
<b>Ambient temperature</b>		-20 ... +55 -4 ... +131	°C °F	
<b>Weight</b>		22,7 50.0	kg lbs.	incl. hydraulic fluid, w/o battery incl. hydraulic fluid, w/o battery
<b>Weight battery</b>		0,9 2	kg lbs.	
<b>Protection class</b>		IP 54		
<b>Opening / closing time</b>	>	2	s	w/o load
<b>Noise pressure level</b>	idle mode max. load	74 77	dB(A) dB(A)	
<b>Rechargeable battery 1 / 2</b>		25,2 2,6 / 5,0	V DC Ah	Li-Ion, optional accessory
<b>Current consumption</b>		12 40	A A	idle mode max. load
<b>EN 13204 Cutting performance</b>		1K-2K-3K-4K-5K		
<b>Operating pressure</b>		70 10,000	MPa psi	
<b>Note:</b>				
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
<b>LUKAS Hydraulik GmbH</b>	Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394			

Änderungen vorbehalten / Subject to revision