

LUKAS	eDRAULIC Cutter				EN
	S 788 eWXT 90-25-42				
	Technical Data				
Non-metric dimensions are for reference only.					
Nomenclature		Value	Unit	Remark	
Dimensions	L x W x H	904 x 266 x 253 35.6 x 10.5 x 9.96	mm in.	closed; w/o battery	
Cutting performance		Ø42 Ø1.65	mm in.		
Opening width at tips		200 7.87	mm in.	at tips	
Ambient temperature		-20 ... +55 -4 ... +131	°C °F		
Weight		22,2 48.9	kg lbs.	incl. hydraulic fluid, w/o battery incl. hydraulic fluid, w/o battery	
Weight battery 9 Ah		1,6 3.6	kg lbs.		
Weight battery 5 Ah		1,2 2.7	kg lbs.		
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters	
Opening / closing time	>	2	s	w/o load	
Noise pressure level	idle mode max. load	72 73	dB(A) dB(A)		
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory	
Current consumption		7,7 42,2	A A	idle mode max. load	
EN 13204 Cutting performance		1K-2K-3K-4K-5K			
Operating pressure		70 10,000	MPa psi		
Note:					
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.					
LUKAS Hydraulik GmbH	Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394				

Änderungen vorbehalten / Subject to revision