

LUKAS	eDRAULIC Spreader			EN
	SP 333 e³ 93-10-13			
	Technical Data			
Non-metric dimensions are for reference only.				
Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	823 x 256 x 253 32.4 x 10.1 x 9.96	mm in.	closed; w/o battery
Opening width at tips		600 23.6	mm in.	
Force / spreading	min.	42 9442	kN lbf.	25 mm from front end of tips
Force / spreading	max.	836 187940	kN lbf.	
Force / pulling	max.	56 12589	kN lbf.	with chain set KSV 11
Pulling distance		440 17.3	mm in.	with chain set KSV 11
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Weight		17,1 37.7	kg lbs.	incl. hydraulic fluid, w/o battery
Weight battery 9 Ah		1,6 3.6	kg lbs.	
Weight battery 5 Ah		1,2 2.7	kg lbs.	
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters
Opening / closing time	>	2	s	w/o load
Noise pressure level	idle mode max. load	68 77	dB(A) dB(A)	nach EN 13204 nach EN 13204
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory
Current consumption		7,3 41,8	A A	<i>idle mode</i> <i>max. load</i>
Operating pressure		70 10,000	MPa psi	
Note:				
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
LUKAS Hydraulik GmbH	Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394			

Änderungen vorbehalten / Subject to revision