

**LUKAS****eDRAULIC Combistool  
SC 758 eWXT 90-35-35****EN**

Technical Data

*Non-metric dimensions are for reference only.*

Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	987 x 266 x 253 38.9 x 10.5 x 9.96	mm in.	closed; w/o battery
Cutting performance		Ø 40 Ø 1.58	mm in.	acc. to EN 13204 / NFPA 1936
Opening width at tips		475 18.7	mm in.	at tips
Opening width cutting	min.	400 15.7	mm in.	end of cutting area
Force / spreading	min.	43 9667	kN lbf.	25 mm from front end of tips
Force / spreading	max.	1500 337213	kN lbf.	
Force / cutting	max.	885 198955	kN lbf.	
Force / pulling	max.	94 21132	kN lbf.	with chain set KSV 13 and adapter set
Pulling distance		340 13.4	mm in.	with chain set KSV 13 and adapter set
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Weight		24 52.9	kg lbs.	incl. hydraulic fluid, w/o battery
Weight battery 9 Ah		1,6 3.6	kg lbs.	
Weight battery 5 Ah		1,2 2.7	kg lbs.	
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters
Opening / closing time	>	2	s	
Noise pressure level	idle mode max. load	72 73	dB(A) dB(A)	
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory
Current consumption		7,3 40,4	A A	idle mode max. load
EN 13204 Cutting performance		1J-2K-3K-4K-5K		
Operating pressure		70 10,000	MPa psi	

Note:

Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.

**LUKAS Hydraulik GmbH**

Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394

Änderungen vorbehalten / Subject to revision