

LUKAS**eDRAULIC RAM
R 521 e³ 93-40-12****NFPA**

Technical Data

Non-metric dimensions are for reference only.

Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	579 x 140 x 324 22.8 x 5.51 x 12.9	mm in.	retracted, w/o battery
Length extended		1359 44.3	mm in.	
Stroke	piston 1	403 15,6	mm in.	
Force / spreading HSF	piston 1	127 28600	kN lbf.	Highest Spreading Force
Stroke	piston 2	377 14.8	mm in.	
Force / spreading HSF	piston 2	60 13500	kN lbf.	Highest Spreading Force
Stroke	total	780 30.7	mm in.	
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Weight		19 41.9	kg lbs.	incl. Hydraulic fluid, w/o battery
Weight battery 9 Ah		1,6 3.6	kg lbs.	0
Weight battery 5 Ah		1,2 2.7	kg lbs.	
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters
Extending / retracting time	>	2	s	w/o load
Noise pressure level	idle mode max. load	61 69	dB(A) dB(A)	acc. to NFPA 1936 acc. to NFPA 1936
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory
Current consumption		7,3 42,7	A A	idle mode max. load
Operating pressure		50	MPa	
Note:	Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.			
LUKAS Hydraulik GmbH	Weinstraße 39 • D-91058 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394			

Änderungen vorbehalten / Subject to revision